

ImagePerfect[™] 2420 Plus ETU Wallpaper (FR)

ImagePerfect™ 2420 Plus ETU Wallpaper is a washable, non-woven paper with a smooth surface for wall decoration. It is pre-coated with paste. Simply dip the printed product into a tray of water and then apply directly to the substrate. This product has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

ImagePerfectTM 2420 Plus ETU Wallpaper is a printable, high-quality, non-woven wallpaper with a high level of opacity. It can be used to personalise home interiors, retail spaces, show rooms, trade shows, hotels, restaurants and many more environments. It promotes high levels of print quality with remarkable text definition and a large colour gamut to ensure colourful images with vibrant area infills. It incorporates high levels of dimensional stability and generates no shrinkage. As such, individual panels do not need to be overlapped; they can simply be applied side-by-side on the substrate with no risk of subsequent separation. IP 2420 Plus is already pre-coated with paste. For the best application results, the IP 2420 Plus should be dipped into a tray of water (for no less than 15 seconds and for no longer than 30 seconds) and then applied directly to the substrate. While the paste is wet, the IP 2420 Plus remains repositionable and so can be readily moved on the substrate to slide the wallpaper panels into place. In comparison to using a traditional wallpaper, with the need to apply a conventional paste, it is expected that the use of IP 2420 Plus will reduce the application time by more than 50%. The printed graphics are very scrub-resistant and can be cleaned with warm water, soap and a soft sponge. This product is PVC-free and it meets the requirements of ISO 14001 and other key environmental reference points within the paper industry and it can be validated, therefore, as being sustainable, environmentally-friendly and ecologically produced, with the production of the wood that is used in the production of the paper being a socially and environmentally responsible process.

Attention: It is important to use the matched print profile for this product as vertically-applied graphics may otherwise delaminate from the substrate as a result of increased surface tension (caused by ink oversaturation). It is strongly recommended for the printed media to lay flat during the drying process. Please ensure that the printed IP 2420 Plus is completely dry before application. Please ensure that the surface is perfectly clean, completely dry and primed before application of the IP 2420 Plus. Upon application of IP 2420 Plus, the surface should be dried immediately, ensuring that any residual water and paste is completely removed.

Specifications	
Description	Wallpaper
Colour	White semi-matt
Thickness	330mym
Weight	225g/m ²
Adhesive	Acrylic, permanent
Temperature Range	N/A
Durability (unprinted)	N/A
Flame Retardancy	D-s1, d0
Shelf Life	2 years, 20°C / 50% humidity

May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom