

ImagePerfect[™] 2505PA Plus White Matt Polymeric Vinyl (FR)

ImagePerfect™ 2505PA Plus is a white matt polymeric vinyl incorporating PerfectApply technology and a permanent solvent-based adhesive. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

ImagePerfect™ 2505PA Plus utilises a heavy 100mym, opaque, white vinyl with a matt finish that gives the product body and rigidity, thereby ensuring ease of handling during application, particularly with large graphics. As such, it is ideal for applications such as markings and decorations on trucks, railway carriages, busses, boats, recreational vehicles, vending machines, shipping containers, POP display and architectual graphics. Additional opacity is provided by the permanent grey adhesive and the incorporation of PerfectApply technology increases repositionability during application and facilitates a bubble-free finish. The film incorporates specific polymeric, non-migrating plasticisers and UV-stabilisers, which ensure long-term outdoor durability. With heat it can be easily removed. It must not be wet applied - i.e. dry application only. Laminate: IP 2810-101, IP 2810-200, IP 2810-300, IP 2830-106, IP 2830-109, IP 2830-200.

Attention: Please make sure the printed IP 2505PA Plus is completely dry before laminating. Before the IP 2505PA Plus is applied, the surface should be completely cleaned. The use of IP Surface Cleaner (MIP1000) and the lint-free, IP Surface Cleaning Cloths (MMS8373) is a good match component cleaning solution to ensure that the surface is dry and free of dust and grease.

| Specifications | |
|------------------------|---|
| Description | Polymeric vinyl |
| Colour | White matt |
| Thickness | 100mym |
| Weight | N/A |
| Adhesive | Solvent based acrylic, permanent, grey |
| Adhesive Strength | 18N/25mm (Finat TM 1/24h) |
| Release Paper | PE-coated silicone paper, 140g/m ² |
| Temperature Range | -30°C to +90°C |
| Durability (unprinted) | 7 years |
| Flame Retardancy | B1 |
| Shelf Life | 2 years, 20°C / 50% humidity |
| End of Life / Disposal | Not currently recyclable. Can be used for refuse derived fuel (RDF) |

May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom