

ImagePerfect[™] 2522 White Eco Digital Media (FR)

ImagePerfect™ 2522 is a white cast polypropylene for the creation of more environmentally-friendly printed output than would otherwise be the case with vinyl products. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

ImagePerfectTM 2522 utilises a 100% PVC-free film with a special top-coat to facilitate printability of the highest quality, with remarkable text definition and vibrant area in-fills. It is suitable for all indoor applications and, because the film offers good levels of UV-resistance, it is also suitable for outdoor applications with up to 2 year durability. It is plasticiser-free, chlorine-free and environmentally-friendly. Unlike PVC, on incineration, this product will not release dioxin, thereby allowing for non-hazardous disposal. It also meets the full requirements of the EU Phthalates Directive 2005/84/EC, concerning phthalates content in childrens' toys and articles, together with EN 71 (Part 3) as the European standard specifying the legal safety requirements for all toys. Added-value printed output would include all manner of decals, self-adhesive stickers, decoration and signage for hospitals and retail food departments in which the use of products containing plasticiser is typically highly regulated. Laminate: IP 2840-106.

Attention: Please make sure the printed IP 2522 is completely dry before laminating. Before the IP 2522 is applied, the surface should be completely clean. The use of IP Surface Cleaner (MIP1000) and the lint-free, IP Surface Cleaning Cloths (MMS8373) is a good match component cleaning solution to ensure that the surface is dry and free of dust and grease.

Specifications	
Description	Cast polypropylene
Colour	White gloss
Thickness	95mym
Weight	N/A
Adhesive	Acrylic, semi-permanent
Adhesive Strength	11N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone kraft, 140g/m²
Temperature Range	-20°C to +90°C
Durability (unprinted)	2 years
Flame Retardancy	B1
Shelf Life	2 years, 20°C / 50% humidity

May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom