

ImagePerfect[™] 2525PA White Gloss Monomeric Vinyl (FR)

ImagePerfect™ 2525PA is a white gloss monomeric vinyl incorporating PerfectApply technology and a grey, removable adhesive for indoor and outdoor applications. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks (with the exception of 3rd generation inks when used with 300 series printers).

ImagePerfectTM 2525PA White Gloss Monomeric Vinyl is a removable product for indoor and outdoor applications on flat, smooth surfaces, such as point-of-sale and promotional installations. It incorporates PerfectApply technology to increase repositionability during installation and to facilitate bubble-free application. It promotes high levels of print quality with remarkable text definition and a large colour gamut to ensure colourful images with vibrant area in-fills. It is equipped with a backing paper that offers excellent lay flat properties. Additional opacity is provided by the grey adhesive. It must not be wet applied - i.e. dry application only. Laminate: IP 2820-101, IP 2820-200, IP 2830-109, IP 2830-200, etc.

Attention: Please make sure the printed IP 2525PA is completely dry before laminating. Before the IP 2525PA is applied, the surface should be completely cleaned. The use of IP Surface Cleaner (MIP1000) and the lint-free, IP Surface Cleaning Cloths (MMS8373) is a good match component cleaning solution to ensure that the surface is dry and free of dust and grease. Please note: When the product is converted on an HP 500 series printer, it is essential that the "cleaning cylinder" is used.

| Specifications | |
|------------------------|-----------------------------------|
| Description | Monomeric vinyl |
| Colour | White gloss |
| Thickness | 100mym |
| Weight | N/A |
| Adhesive | Acrylic, removable, grey |
| Adhesive Strength | 7N/25mm (Finat TM 1/24h) |
| Release Paper | PE-coated silicone paper, 140g/m² |
| Temperature Range | -40°C to +80°C |
| Durability (unprinted) | 3 years |
| Flame Retardancy | B1 |
| Shelf Life | 2 years, 20°C / 50% humidity |

May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom