

ImagePerfect[™] 2578PA 2D Wrap (FR)

ImagePerfect™ 2578PA 2D Wrap incorporates a special 50mym white gloss supersoft print film for use in fleet and vehicle applications with 2D, single-step recesses. It incorporates PerfectApply technology for easy positioning and bubble-free application. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

ImagePerfect™ 2578PA 2D Wrap is a permanent product for indoor and outdoor applications, such as markings, decorations and vehicle graphics, including fleet vehicles with compound curves and moderate (2D, single-step) recesses that would otherwise dictate the use of a more expensive product. The thin, supersoft print film has been specially engineered to promote flexibility and conformability whilst also offering high levels of post-application stability and high levels of print quality with remarkable text definition and a large colour gamut to ensure colourful images with vibrant area in-fills. It also incorporates PerfectApply technology to increase repositionability and to facilitate bubble-free application. It is equipped with a backing paper that offers excellent lay flat properties and an opaque adhesive system to provide a clean backdrop for printed images with no risk of substrate show-through. Laminate: IP 2810-105.

Attention: Please make sure the printed IP 2578PA 2D Wrap is completely dry before laminating. Before the IP 2578PA 2D Wrap is applied, the surface should be completely cleaned. The use of IP Surface Cleaner (MIP1000) and the lint-free, IP Surface Cleaning Cloths (MMS8373) is a good match-component cleaning solution to ensure that the surface is dry and free of dust and grease. In order to ensure the best results, this product should be dry applied.

Specifications	
Description	Long-term supersoft print film
Colour	White gloss
Thickness	50mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent, grey
Adhesive Strength	18N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 140g/m²
Temperature Range	-30°C to +90°C
Durability (unprinted)	8 years
Flame Retardancy	B1
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom