

ImagePerfect™ 2595R9C CarpetApp (FR)

ImagePerfect™ 2595R9c CarpetApp is a white textured vinyl with a with a non-slip surface and a semi-permanent adhesive that is engineered for use in short-term, indoor floor graphic installations on low-pile carpets. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

ImagePerfect™ 2595R9C CarpetApp has been specifically engineered for use as a short-term, printable floor graphic product on low-pile carpets (and carpet tiles). It can be used for installations such as promotional advertising, point-of-sale and point-of-purchase promotions, temporary wayfinding graphics and public information displays. As such, it will be used in retail locations, offices, meeting rooms, hotels, trade shows, exhibitions, airports, museums, cinemas, casinos, etc. It can also be used on the flat areas of most textile seats in locations such as the waiting areas at airports and hospitals, as well as textile seats in public transport such as busses and trains. IP 2595R9C delivers high levels of print quality with a large colour gamut that ensures colourful images with vibrant area in-fills. The adhesive system delivers perfect adhesion on low-pile carpets and should allow for quick and clean removability, leaving no adhesive residue on the substrate after removal of the product. The product does not require the use of an additional laminate, delivering inherent scuff-resistance and a non-slip surface (R9).

Attention: It is strongly recommended for the product to lay flat during the drying process. In order to avoid potential lifting of the product, we would recommend that corners are rounded rather than cut to a sharp 90° angle. Surface preparation: In order to achieve process-secure application, it is essential that the substrate is totally dry and completely free of dust, dirt and debris before the product is installed. As such, we would recommend that the substrate is brushed and vacuumed before the IP 2595R9C is applied and, if the substrate is wet, we would recommend that it should be dried via portable heating, again before the product is installed. For application, the substrate should have a surface temperature of no less than 15°C

Specifications	
Description	Indoor floor graphics on low-pile carpet
Colour	White matt
Thickness	200mym
Weight	N/A
Adhesive	Solvent based, semi-permanent
Adhesive Strength	23±2N/25 mm (Finat TM 1/24h on glass) 5±1N/25 mm (on low-pile carpet)
Non-Slip Rating	R9
Release Paper	PE-coated silicone paper, 140g/m ²
Temperature Range	-30°C to +90°C
Durability (unprinted)	3 months (depending on the application)
Flame Retardancy	B-s1, d0
Shelf Life	1 year, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

© May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Eikon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Eikon's general terms and conditions of sale. Eikon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Eikon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.