

## ImagePerfect<sup>™</sup> 2703 Perforated Window Film

ImagePerfect™ 2703 Perforated Window Film is a white polymeric product with a permanent adhesive and a black backside for use on transparent substrates. The perforations in the film are designed to allow the full image to be seen from the outside of the window, whilst still allowing for viewability through the film from the inside of the window. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks.

ImagePerfect™ 2703 Perforated Window Film should be used on flat glass surfaces and is intended for indoor and short-term outdoor applications. It is an excellent option for retail displays on shop windows, for promotional advertising on cars and public transport vehicles (such as buses, coaches, taxis, trams, etc.) and for decorative applications on other building windows/ glass panels. The perforations in the film are designed to allow the full image to be seen from the outside of the window whilst allowing for viewability through the film from the inside of the window. This product should not be exposed to cleaning fluids that contain solvent or ammonia. To obtain good through vision and protection against moisture and abrasion, we would recommend overlaminating. Laminate: IP 2830-100.

Attention: Please ensure the printed IP 2703 is completely dry before laminating. Before the IP 2703 is applied, the surface should be completely cleaned. The use of IP Surface Cleaner (MIP1000) and the lint-free, IP Surface Cleaning Cloths (MMS8373) is a good match-component cleaning solution to ensure that the surface is dry and free of dust and grease. This product must not be wet applied - i.e. dry application only.

Specifications	
Description	Polymeric PWF / 50% printable surface with 1.5mm holes
Colour	White
Thickness	140mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent, black
Adhesive Strength	12N / 25mm (Finat TM 1/24h)
Release Paper	PE-coated non-perforated silicone paper, 135g/m <sup>2</sup>
Temperature Range	-40°C to +80°C
Durability (unprinted)	4 years
Flame Retardancy	N/A
Shelf Life	2 years, 20°C / 50% humidity

@ May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom