

ImagePerfect™ 2830-111

Clear Gloss SafeTouch Laminate (FR)

ImagePerfect™ 2830-111 is a functional laminate with an antimicrobial additive that has been specifically designed for protecting surfaces in a wide variety of environments.

ImagePerfect™ 2830-111 SafeTouch is a functional laminate containing a highly-effective additive that offers protection from micro-organisms, such as bacteria, viruses, fungi and parasites. Whilst antimicrobial products typically incorporate silver agents, this product utilises zinc pyrithione as its active ingredient and it is encapsulated within the film rather than manifesting as a simple coating on top of the film. As such, the antimicrobial effect is stable and long-lasting. Indeed, when tested independently, the antimicrobial properties were found to be completely unaffected when IP SafeTouch was fully immersed for 1 minute in 3 different solutions of 70.0% ethanol, 0.1% IPA and 5.0% benzalkonium chloride, before being cleaned and dried and then re-immersed for a further minute, with this cycle being repeated 50 times. In accordance with ISO 22196, the antimicrobial properties of IP SafeTouch demonstrate antibacterial activity of >99.99% after a contact time of 24 hours. This has been substantiated with testing against specific bacteria that include Escherichia Coli (E. Coli), Staphylococcus Aureus (Golden Staph), Methicillin-Resistant Staphylococcus Aureus (MRSA), Salmonella, Listeria, Klebsiella Pneumoniae (K. Pneumoniae), Enterococcus Faecalis (E. Faecalis), Pseudomonas Aeruginosa and Legionella Pneumophila. In accordance with ISO 21702, the antimicrobial properties of IP SafeTouch demonstrate antiviral activity of 74.30% (1.3 log₁₀ TCID₅₀) on human coronavirus HCoV-229E after a contact time of 24 hours (measured at 25°C with a relative humidity of 90%). IP SafeTouch can be used on many different kinds of flat surface, including doors, desks, tables, counters, cupboards, shelves, windows and panels, and it can be used in a wide variety of environments, such as RETAIL SPACES (shopping centres, supermarkets, barbering shops, etc), HEALTHCARE ENVIRONMENTS (hospitals, clinics, doctors' surgeries, etc), EDUCATIONAL FACILITIES (nurseries, schools, universities, etc), PUBLIC TRANSPORT (taxis, busses, trains, etc), LIFESTYLE ENVIRONMENTS (hotels, restaurants, cafes, bars, gyms, etc) and EVENT BUSINESS LOCATIONS (exhibition centres, conference facilities, meeting rooms, etc). However, we would not recommend this product for use in environments in which it could be subject to direct food contact (such as kitchens, food preparation areas, food processing plants, etc). When used as a protective laminate on printed output, it supports compatibility with different grades of calendered PVC. In such cases, the printed media must be left to "dry" for at least 48 hours before being laminated with IP SafeTouch, otherwise the antimicrobial properties could be negatively impacted. In application, IP SafeTouch has a high level of transparency, thereby retaining the aesthetic of the surface to which it is applied and, when applied to an appropriate substrate, it will support removability with easy clean properties in the event of any adhesive transfer. Surface preparation: Before IP SafeTouch is applied, the surface should be completely cleaned. The use of IP Surface Cleaner (MIP1000) and the lint-free, IP Surface Cleaning Cloths (MMS8373) is a good match-component cleaning solution to ensure that the surface is dry and free of dust and grease.

Specifications	
Description	Surface protection laminate
Colour	Clear gloss
Thickness	80μm
Weight	N/A
Adhesive	Solvent based acrylic, semi-permanent
Adhesive Strength	10N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 140g/m ²
Temperature Range	-30°C to +90°C
Durability (unprinted)	3 years
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

© May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Eikon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Eikon's general terms and conditions of sale. Eikon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Eikon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.