

ImagePerfect[™] 2830-200 Clear Matt Scratch-Resistant Laminate (FR)

ImagePerfect™ 2830-200 is an embossed laminate with a permanent, solvent-based adhesive system that has been specifically designed for protecting digital prints from scratching.

ImagePerfect™ 2830-200 is an embossed laminate that can be used to provide an enhanced scratch-resistant finish on a wide of clean, dry surfaces. This film is resistant to most mineral oils, fats and fuels, aliphatic solvents, mild acids, alkali solutions and soap suds. It can also be used as a laminate on pop-up media (such as IP 2910 and IP 2916) to provide enhanced scratch-resistance and additional body/rigidity.

Specifications	
Description	Embossed laminate
Colour	Clear matt
Thickness	100mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent
Adhesive Strength	20N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 140g/m ²
Temperature Range	-30°C to +90°C
Durability (unprinted)	3 years
Flame Retardancy	B1
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

[@] May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom