

## ImagePerfect<sup>™</sup> 2830-203 Clear Matt Outdoor Floor Graphics Laminate

ImagePerfect™ 2830-203 is an embossed laminate with a permanent adhesive system that has been specifically designed for protecting outdoor floorminder graphics. It delivers an R9-rated non-slip surface.

ImagePerfect<sup>TM</sup> 2830-203 is a textured laminate that provides a non-slip (R9), scuff-resistant surface finish with high resistance to wearing. In application, it has a high level of transparency. It should be used as a match-component laminate in conjunction with IP 2539 as the harmonised print media for outdoor floor graphic installations. In order to avoid potential lifting of the product, we would recommend that corners are rounded rather than cut to a sharp 90° angle. This laminate must be applied dry (not compatible with wet application).

Specifications	
Description	Outdoor floorminder laminate
Colour	Clear matt
Thickness	125mym
Weight	N/A
Adhesive	Acrylic, permanent
Adhesive Strength	18N/25mm (Finat TM 1/24h)
Non-Slip Rating	R9
Release Paper	Clay-coated kraft, 63g/m²
Temperature Range	-30°C to +90°C
Durability (unprinted)	6 months
Flame Retardancy	N/A
Shelf Life	2 years, 20°C / 50% humidity

<sup>@</sup> May 2022 Elkon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom