

ImagePerfect™ 2830-205

Clear Matt UV Print Laminate (FR)

ImagePerfect™ 2830-205 is a polymeric laminate with a permanent, solvent-based adhesive system that has been specifically engineered for laminating UV prints.

ImagePerfect™ 2830-205 has been specifically engineered to allow for the lamination of UV prints that are otherwise difficult to laminate because of the fact that the low-energy nature of the printed output makes it challenging to establish any sort of adhesive bond with the laminate. This laminate option even works effectively on large areas of dark, block UV print which generally have lower peel values than areas that are covered with light-coloured print and are, therefore, even more problematic in terms of establishing an adhesive bond with the product. IP 2830-205 can be used as a laminate option for cast, polymeric and monomeric products. Please note that it should not be used in conjunction with high-pressure washing systems as it would increase the risk of the product losing its adhesive bond with the substrate.

Specifications	
Description	UV print laminate
Colour	Clear matt
Thickness	70mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent
Adhesive Strength	20N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 140g/m ²
Temperature Range	-30°C to +90°C
Durability (unprinted)	6 years
Flame Retardancy	B1
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

© May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Eikon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Eikon's general terms and conditions of sale. Eikon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Eikon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.