

ImagePerfect[™] 2910 Plus Pop-Up Display (FR)

ImagePerfect™ 2910 Plus is a white, matt display material with excellent layflat properties for use in pop-up systems. This product has been specially created for digital printing on large-format inkjet and is suitable for printing with eco solvent and solvent inks.

ImagePerfect™ 2910 Plus has excellent layflat properties and its rigid nature makes it an ideal choice for use in pop-up systems, as seen in retail locations, conference centres, exhibition halls and lifestyle business locations (such as hotels, casinos, sports arenas, etc). This material can be used in conjunction with self-adhesive, 12.5mm magnetic strips (MAGHCM51930) to allow for easy attachment to the pop-up frame. It can be score cut on almost any plotter. A 45° tangential blade should be used but a 45° swivel blade can be substituted for simple shapes. Plotter speed should be slowed to 60%. Optimal weeding results will be achieved if shapes with sharp corners are assigned a radius of at least 1/10" (2.54mm) [use the "Fillet Corner" feature]. Small shapes may be difficult to weed; the user should determine sizes appropriate to the design of the graphic. The ideal score cut will penetrate halfway through the material. To remove the finished pieces, the material should be folded backwards along a straight-cut line. When pinched, the material should separate from the waste matrix. Slowly remove the finished piece, one edge at a time. A test cut is advisable to determine if the tool force setting needs to be adjusted for the specific application. Important recommendation: To protect the printed surface from abrasion, dirt or humidity, and to also provide additional body and rigidity, we would recommend the use of a filmic overlaminate. The IP 2910 Plus must be completely dry prior to application of the laminate. Laminate: IP 2830-200.

Specifications	
Description	Semi-rigid PVC pop-up media
Colour	White matt
Thickness	450mym
Weight	635g/m ²
Temperature Range	-10°C to +55°C
Durability (unprinted)	N/A
Flame Retardancy	B1
Shelf Life	2 years, 20°C / 50% humidity

May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom