

ImagePerfect™ 7504

Screen Privacy Film

When applied to glass, ImagePerfect™ Screen Privacy Film preserves perfect viewability through the glass whilst creating a blackout effect on LED and LCD screens.

When applied to glass, ImagePerfect™ Screen Privacy Film uses polarising technology to preserve perfect viewability through the glass whilst creating a blackout effect on any LED and/or LCD screens that are behind the glass. It will be used to ensure privacy of information and to prevent data theft via visual hacking in corporate and municipal environments such as banks, government buildings, legal offices, meetings rooms and conference facilities, as well as in other consultative locations such as medical environments. It utilises a high-quality PET film with a hard, scratch-resistant surface for durability and ease of maintenance during window cleaning.

INSTALLATION: The film should be installed on the glass vertically or horizontally at an angle of 45° (not skewed/slanted) but the specific direction in which the film should be applied will vary by screen technology. We would then recommend a test before installation in order to ensure the correct alignment with the screen and also to ensure that the film will function properly (some screen technologies, such as plasma, are unlikely to work with the film). The film should be handled with caution because the edges are sharp. In order to prevent the film from splitting, it should be pre-cut before installation on a flat surface. It must be wet applied (we would recommend a pH neutral baby shampoo). After installation, in order to prevent the film from developing subsequent movement, ensure that the edges of the film have been thoroughly dried. In the event of a join being needed, a minimum 2mm gap should be left between the panels. To prevent tunnelling, any unused film should be stored wound on its original core. Do not clean for at least 1 month after installation and do not use abrasive cleaning products, including ammonia, brushes and scrapers as these are likely to damage the surface of the film.

Attention: Do not clean for at least 1 month after application and do not apply any type of sticker or adhesive on the film.

Specifications	
Description	Polyester + PVA
Installation	Interior
Colour from the outside	Clear
Thickness	132mym
Adhesive	Solvent based acrylic, permanent
Visible Light Transmission	N/A
Durability (unprinted)	5 years
Flame Retardancy	M1
Shelf Life (at -5°C to +40°C)	1 year
End of Life / Disposal	N/A

© May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Eikon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Eikon's general terms and conditions of sale. Eikon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Eikon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.