

ImagePerfect[™] 7804PA Light Silver Frost (FR)

ImagePerfect™ Light Silver Frost is a polymeric, semi-opaque, matt calendered vinyl, incorporating PerfectApply technology and a permanent, solvent-based adhesive. It is used for decorative window installations, both cut graphics and also printed graphics.

ImagePerfect™ Light Silver Frost is a semi-opaque, matt, calendered vinyl that is suitable for use on a wide variety of clean, dry surfaces. It will be primarily used as a decorative window film to create an etched (engraved) effect on windows or glass panels in architectural enhancement and advertising/display installations in locations such as retail environments and lifestyle business environments (bars, hotels, restaurants, casinos, theatres, etc). It will also be used for glass conspicuity for personal safety in locations with high footfall, such as shopping centres and educational establishments. The specially-formulated, flexible film has consistent matt levels and it delivers a high degree of dimensional stability and colourfastness and it can be cut easily and weeded quickly and the high-quality, PE-coated liner further promotes excellent layflat, cutting and weeding characteristics. The permanent, solvent-based adhesive creates a strong final bond to ensure a secure and durable finish. It incorporates PerfectApply technology to increase repositionability during installation and to facilitate a bubble-free finish, especially in the case of large, flat-panel installations. The metallic effect in the film delivers a more dynamic visual impact than would otherwise be the case with a "standard" frost/crystal film. For digital conversion, it is compatible with eco solvent, solvent, latex and UV-cured inks, to which end it will deliver high levels of print quality with remarkable text definition and a large colour gamut, ensuring colourful images with high black values and vibrant area in-fills. Laminate: IP 2810-200. In order to retain the crystal look of the product, it is important that this match-component crystal laminate is used (and not a standard gloss or matt laminate). In order to ensure the best results, this product must be dry applied. In application, the film will absorb just 3.8% of visible light / transmit 96.2% of visible light.

Attention: If printing, please make sure the printed media is completely dry before laminating. Before the media is applied, the surface should be completely cleaned. The use of IP Surface Cleaner and lint-free, IP Surface Cleaning Cloths is a good match component cleaning solution to ensure that the surface is dry and free of dust and grease.

Specifications	
Description	Polymeric calendered vinyl
Colour	Semi-opaque silver matt
Thickness	80mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent
Adhesive Strength	20N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 140g/m²
Temperature Range	-30°C to +90°C
Durability (unprinted)	8 years
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

© May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom