

ImagePerfect™ 7811 WindowTex Pebble (FR)

ImagePerfect™ WindowTex is a semi-transparent, self-adhesive textile that is used to create decorative features on indoor glass surfaces, ranging from stand-alone graphics to larger-scale window coverage.

ImagePerfect™ WindowTex Pebble is a grey, semi-transparent, self-adhesive textile that is used to create decorative features on indoor, smooth, flat surfaces, such as stainless steel and lacquered substrates but it will be most commonly used on glass, ranging from stand-alone graphics to larger-scale window coverage. It is ideal for architectural enhancement in retail environments and lifestyle business environments (bars, hotels, restaurants, casinos, theatres, etc). It will also be used for glass conspicuity (for reasons of personal safety) in locations with high footfall, such as shopping centres and educational establishments, and it will also add an element of privacy screening in corporate and commercial environments, without blocking the inside to outside view. It can be kiss-cut with a variety of flat-bed cutters. It is easy to install and, whilst simple shapes could be applied direct, we would recommend the use of a high-tack application tape for the installation of more complex shapes. The adhesive is repositionable during installation but, once mounted with squeegee pressure, the film should not be removed as re-application might not be possible (due to a drop in adhesive strength). Under normal conditions, IP WindowTex will not cause thermal stress on glass but the risk is increased in the case of graphics that are exposed to direct sunlight with uneven exposure. Please refer to the IP 7800 WindowTex Application Guidelines and After-Care Recommendations for additional insights. This product is not compatible with digital conversion; for a printable option, please refer to IP 7810 WindowTex White. This product must be applied dry and in dry conditions. Installation should be avoided in environments in which there is a risk of moisture being present (including condensation) as this could negatively impact the adhesive properties. In application, the film will absorb 32.0% of visible light / transmit 47.0% of visible light.

Specifications	
Description	100% woven polyester
Colour	Grey
Thickness	245mym
Weight	95g/m ²
Adhesive	Acrylic, repositionable removable
Adhesive Strength	N/A
Release Liner	Polyester, 105g/m ²
Temperature Range	-20°C to +50°C
Durability (unprinted)	5 years
Flame Retardancy	B-s1, d0
Shelf Life	1 year
Storage	In a dark location, at 10°C – 35°C and a relative humidity of 35% - 55%
End of Life / Disposal	N/A
Application Temperature	> 5°C
Textile Openness	17%
Transparency Factor (0 - 4)	2 (moderate effect)
Visible Light Transmission	47%

© May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Eikon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Eikon's general terms and conditions of sale. Eikon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Eikon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.