

ImagePerfect[™] iD1 Perforated Window Film 70/30

ImagePerfect™ iD1 Perforated Window Film is a white, short-term calendared vinyl with a removable adhesive, and a black backside for use on transparent substrates. The perforations in the film are designed to allow the full image to be seen from the outside of the window, while still allowing for viewability through the film from the inside of the window. It is designed for digital printing with large-format inkjet printers and is compatible with eco-solvent, solvent, UV-cured, and latex inks.

ImagePerfectTM iD1 Perforated Window Film feature a unique dual-layer liner that enables printing on all printer types including solvent, eco-solvent, latex, and UV, without risk of the ink clogging the perforation holes. IP iD1 should be used on flat glass surfaces and is intended for indoor and short-term outdoor applications. It is an excellent option for retail displays on shop windows, for promotional advertising on cars and public transport vehicles (such as buses, taxis, trams, etc.) and for decorative applications on other building windows/glass panels. The perforations in the film are designed to allow the full image to be seen from the outside of the window while allowing for viewability through the film from the inside of the window. This product should not be exposed to cleaning fluids that contain solvent or ammonia. To obtain good through vision and protection against moisture and abrasion, we would recommend overlaminating with IP iD5 OptiClear.

Attention: Please ensure the printed IP iD1 is completely dry before laminating. Before the product is applied, the surface should be completely cleaned. This product must not be wet applied - i.e. dry application only.

Specifications	
Description	Short-term calendared vinyl / 70% printable surface with 60mil holes
Color	White
Thickness	6mil
Weight	N/A
Adhesive	Solvent based acrylic, removable, black
Adhesive Strength	N/A
Liner	Dual laminated liner, 90#
Temperature Range	-4°F to +158°F
Durability (unprinted)	1 year
Flame Retardancy	N/A
Shelf Life	6 months, 68°F / 50% humidity

® November 2023 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect™, please visit www.eikonmaterials.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom