

## ImagePerfect<sup>™</sup> iD7 Satin Crystal

ImagePerfect™ iD7 Satin Crystal is a hi-performance calendared, transparent matte vinyl with a permanent, solvent-based adhesive. It is used for decorative window installations, both cut graphics and also printed graphics.

ImagePerfect<sup>TM</sup> iD7 Satin Crystal is a transparent, matte, hi-performance calendared vinyl that is suitable for use on a wide variety of clean, dry surfaces. It will be primarily used as a decorative window film to create an etched (engraved) effect on windows or glass panels in architectural enhancement and advertising/display installations in locations such as retail environments and lifestyle business environments (bars, hotels, restaurants, casinos, theaters, etc). It will also be used for glass conspicuity for personal safety in locations with high footfall, such as shopping centers and educational establishments. The specially-formulated, flexible film has consistent matt levels and it delivers a high degree of dimensional stability and colorfastness and it can be cut easily and weeded quickly and the high-quality, PE-coated liner further promotes excellent layflat, cutting and weeding characteristics. The permanent, solvent-based adhesive creates a strong final bond to ensure a secure and durable finish. For digital conversion, it is compatible with eco solvent, solvent, latex and UV-cured inks, it will deliver high levels of print quality with remarkable text definition and a large color gamut, ensuring colorful images with high black values and vibrant area in-fills. In application, the film will absorb 15.3% of visible light / transmit 84.7% of visible light.

Attention: If printing, please make sure the printed media is completely dry before laminating. Before the media is applied, the surface should be completely cleaned. The use of IP Surface Cleaner and lint-free IP Surface Cleaning Cloths are a good match component cleaning solution to ensure that the surface is dry and free of dust and grease.

Specifications	
Description	Hi-Performance Calendared Vinyl
Color	Transparent matte
Thickness	2.9mil
Weight	N/A
Adhesive	Solvent based acrylic, permanent
Adhesive Strength	4.5lbs/in (Finat TM 1/24h)
Liner	PE-coated silicone paper, 90#
Temperature Range	-22°F to +194°F
Durability (unprinted)	7 years
Flame Retardancy	N/A
Shelf Life	2 years, 68°F / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

© November 2023 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect<sup>TM</sup>, please visit www.eikonmaterials.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom