

No.: XMIN2003001267CM

Date: Apr 01, 2020

Page: 1 of 6



CUSTOMER NAME: SPANDEX AG

ADDRESS: AEGERTWEG 4, 8305 DIETLIKON, SWITZERLAND

Sample Name : PVC ADHESIVE VINYL

Material and Mark : Polymeric Vinyl

Model. : IP 2506 Pro/IP 2506PA Pro

Model for testing : IP 2506 Pro

Above information and sample(s) was/were submitted and confirmed by the client. SGS, however, assumes no responsibility to verify the accuracy, adequacy and completeness of the sample information provided by client.

SGS Ref. No. : SDFS2003001065FF

Date of Receipt : Mar 13, 2020
Testing Start Date : Mar 13, 2020
Testing End Date : Apr 01, 2020

Test result(s) : For further details, please refer to the following page(s)

(Unless otherwise stated the results shown in this test report refer only to

the sample(s) tested)

Signed for SGS-CSTC Standards Technical Services Co., Ltd Xiamen Branch Testing Center

Bryan Hong

Authorized signatory



Inless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer, werleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents within the first of the description of the company in the state of the s



No.: XMIN2003001267CM

Date: Apr 01, 2020

Page: 2 of 6

Test Result Summary

Test(s) Requested	Result(s)	
EN 13501-1:2018 Fire classification of construction products and building elements-Part 1: Classification using data from reaction to fire tests	Classification: B-s1, d0	

Summary:

1. For further details, please refer to the following page(s).

Note: The above test was carried out by SGS-CSTC Standards Technical Services Co., Ltd. Shunde Branch.

SAMPLE INFORMATION AND PICTURES

Mass per unit area: About 129 g/m²



Before Test (EN 13823)



After Test (EN 13823)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions, aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fulles tent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 361101 t (86-592) 5765857 f (86-592) 5765380 www.s.gsgroup.com.cn 中国・福建・厦门・火炬(翔安)产业区翔虹路31号 邮编:361101 t (86-592) 5765857 f (86-592) 5765380 e sgs.china@sgs.com



No.: XMIN2003001267CM

Date: Apr 01, 2020

Page: 3 of 6

TESTS AND RESULTS

Test Conducted:

This test is conducted as per EN 13501-1:2018 Fire classification of construction products and building elements-Part 1: Classification using data from reaction to fire tests. And the test methods as following:

- EN 13823:2010+A1:2014 Reaction to fire tests for building products-Building products excluding floorings exposed to the thermal attack by a single burning item.
- 2. EN ISO 11925-2:2010+AC:2011 Reaction to fire tests-Ignitability of building products subjected to direct impingement of flame-Part 2: Single-flame source test.

Mounting and fixing (For EN 13823:2010+A1:2014):

As per client's requirement, the sample was self adhesive to the substrate (test substrates is calcium silicate board meets the requirement of EN13501-1 of Class A2-s1,d0, the density of 900 kg/m³ and thickness of 10mm).

Test Results:

Test method	<u>Parameter</u>	Number of tests	<u>Results</u>
EN 13823:2010+A1:2014	FIGRA _{0.2MJ} (W/s)		30.3
	FIGRA _{0.4MJ} (W/s)		26.7
	THR _{600s} (MJ)		1.7
	SMOGRA (m²/s²)] 3	2.0
	TSP _{600s} (m ²)]	14.2
	LFS < edge of specimen		Yes
	Flaming particles or droplets		No
EN ISO 11925-	<i>F</i> s ≤ 150 mm		Yes
2:2010+AC:2011 Exposure = 30 s	Ignition of the filter paper	12	No

Remark:

FIGRA-Fire growth rate index used for classification purposes [W/s]

For the classes A2 and B, FIGRA_{0.2}MJ

For the classes C and D, FIGRA_{0.4}MJ

LFS-Lateral flame spread [m]

THR_{600s}-Total heat release within 600 s [MJ]

SMOGRA-Smoke growth rate [m²/s²]

 TSP_{600s} -Total smoke production within $600 \ s \ [m^2]$



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Ferms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fulles that of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 361101 t (86-592) 5765857 f (86-592) 5765380 www.sgsgroup.com.cn 中国 •福建 • 厦门 • 火炬(翔安)产业区翔虹路31号 邮编:361101 t (86-592) 5765857 f (86-592) 5765380 e sgs.china@sgs.com



No.: XMIN2003001267CM

Date: Apr 01, 2020

Page: 4 of 6

Classification and direct field of application:

This classification has been carried out in accordance with EN 13501-1:2018.

Classification:

Fire behaviour	Smoke p	roduction		Flaming	droplets
В	S	1	,	d	0

Remark:

The classes with their corresponding fire performance are given in Table 1.

Reaction to fire classification is based on the 7-step scale of A1 to F, where A1 is good and F is bad

Statement:

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

Warning:

This classification report does not represent type approval or certification of the product. The test laboratory has, therefore, play no part in sampling the product for the test, although it holds appropriate references to the manufacturer's factory production control that is aimed to be relevant to the samples tested and that will provide for their traceability.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Ferms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is client in formation contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fulles then of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 361101 t (86-592) 5765857 f (86-592) 5765380 www.sgsgroup.com.cn 中国・福建・厦门・火炬(翔安)产业区翔虹路31号 邮编:361101 t (86-592) 5765857 f (86-592) 5765380 e sgs.china@sgs.com



No.: XMIN2003001267CM

Date: Apr 01, 2020

Page: 5 of 6

Table 1 — Classes of reaction to fire performance for construction products excluding floorings and linear pipe thermal insulation products.

Class	Test method(s)		Classification criteria	Additional classification
A1	EN ISO 1182 a and		Δ T≤30°C, and Δ m≤50%, and t _i =0(i.e. no sustained flaming)	-
	EN ISO 1716		PCS≤2.0MJ/kg ^a and PCS≤2.0MJ/kg ^{b c} and PCS≤1.4MJ/m ^{2 d} and PCS≤2.0MJ/kg ^e	-
A2 EN ISO 171	EN ISO 1182 ^a or	and	 ∆ T≤50°C, and ∆ m≤50%, and tr≤20 s 	-
	EN ISO 1716		PCS≤3.0MJ/kg ^a and PCS≤4.0MJ/m ^{2 b} and PCS≤4.0MJ/m ^{2 d} and PCS≤3.0MJ/kg ^e	-
	EN 13823		FIGRA≤120W/s and LFS <edge and<br="" of="" specimen="">THR_{600s}≤7.5MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g
EN 13823 and B EN ISO 11925-2 in Exposure = 30s	EN 13823 and		FIGRA≤120W/s and LFS <edge and<br="" of="" specimen="">THR600s≤7.5MJ</edge>	Smoke production ^f and
		Fs≤150mm within 60 s	Flaming droplets/particles ⁹	
C -	EN 13823 and		FIGRA≤250W/s and LFS <edge and<br="" of="" specimen="">THR600s≤15MJ</edge>	Smoke production ^f and Flaming droplets/particles ⁹
	EN ISO 11925-2 i Exposure=30s		Fs≤150mm within 60 s	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/ferms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fulles that the first of the false with the false of the following the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 361101 t (86-592) 5765857 f (86-592) 5765830 www.sgsgroup.com.cn 中国・福建・厦门・火炬(翔安)产业区翔虹路31号 邮编:361101 t (86-592) 5765857 f (86-592) 5765830 e sgs.china@sgs.com



No.: XMIN2003001267CM

Date: Apr 01, 2020

Page: 6 of 6

Class	Test method(s)	Classification criteria	Additional classification	
D	EN 13823 and	FIGRA≤750W/s	Smoke production ^f and	
	EN ISO 11925-2 i Exposure=30s	Fs≤150mm within 60 s	Flaming droplets/particles ⁹	
Е	EN ISO 11925-2 i Exposure =15s	Fs≤150mm within 20 s	flaming droplets/particles h	
F	EN ISO 11925-2 i Exposure =15s	Fs>150mm within 20 s	-	

^a For homogeneous products and substantial components of non-homogeneous products.

 $s1 = SMOGRA \le 30m^2/s^2$ and $TSP_{600s} \le 50m^2$; $s2 = SMOGRA \le 180m^2/s^2$ and $TSP_{600s} \le 200m^2$;

s3 = not s1 or s2

⁹ d0 = No flaming droplets/ particles in EN 13823 within 600 s;

d1 = no flaming droplets/ particles persisting longer than 10 s in EN 13823 within 600 s;

d2 = not d0 or d1.

Ignition of the paper in EN ISO 11925-2 results in a d2 classification.

h Pass = no ignition of the paper (no classification);

Fail = ignition of the paper (d2 classification).

¹ Under conditions of surface flame attack and, if appropriate to the end–use application of the product, edge flame attack.

****** End of report******



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fulles that of the fault unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

No.31 Xianghong Road, Xiang'An Torch Industrial Zone, Xiamen, Fujian Province, China. 361101 t (86-592) 5765857 f (86-592) 5765380 www.sgsgroup.com.cn 中国 •福建 • 厦门 • 火炬(翔安)产业区翔虹路31号 邮编:361101 t (86-592) 5765857 f (86-592) 5765380 e sgs.china@sgs.com

^b For any external non-substantial component of non-homogeneous products.

^c Alternatively, any external non-substantial component having a PCS ≤ 2,0 MJ/m², provided that the product satisfies the following criteria of EN 13823: FIGRA ≤ 20 W/s, and LFS < edge of specimen, and THR_{600s} ≤ 4,0 MJ, and s1, and d0.

^d For any internal non-substantial component of non-homogeneous products.

e For the product as a whole.

fin the last phase of the development of the test procedure, modifications of the smoke measurement system have been introduced, the effect of which needs further investigation. This may result in a modification of the limit values and/or parameters for the evaluation of the smoke production.